

GENLEŞME TANKLARI



SOLAR GENLEŞME TANKI
PN 8 - PN10 (8 LT-1000LT)
110°C
SABİT
MEMBRANLI



CONTRA-FLEX
PN 6 (18 LT-1000 LT)
70°C
SABİT EPDM
MEMBRANLI



FLEXCON
PN 10 (110 LT-1000 LT)
70°C
SABİT BÜTİL
MEMBRANLI



FLEXCON M
PN 6 - PN 10 (80LT-8000 LT)
70°C
DEĞİŞTİRİLEBİLİR
BÜTİL MEMBRANLI



AİRFIX D
PN 8 - PN 10 (8 LT-80 LT)
70°C
SABİT
MEMBRANLI
(TAM HİJYENİK)



AİRFIX P
PN 10 (25 LT-5000 LT)
70°C
DEĞİŞTİRİLEBİLİR
MEMBRANLI
(HİJYENİK)



AİRFIX D-E-B
PN 10 - PN 16 - PN 25
(50 LT-3000 LT)
70°C
DEĞİŞTİRİLEBİLİR
MEMBRANLI
(HİJYENİK)



AİRFIX D-E
PN 10 - PN 16
(50 LT-3000 LT)
70°C
DEĞİŞTİRİLEBİLİR
MEMBRANLI
(HİJYENİK)

Bütün tank çeşitleri anlık ısı yükselmelerinde kısa süreli 120°C'ye kadar dayanıklıdır. Aksi durumlarda danışılmalıdır.